



SPECIFICATIONS



Outdoor Units

VRV X (Cooling Only)

| | |  | |  | | | |
|--------------------|---------------------|---|----------|--|-----------|-----------------|-----------|
| MODEL | | RXQ6ARY1 | RXQ8ARY1 | RXQ10ARY1 | RXQ12ARY1 | RXQ14ARY1 | RXQ16ARY1 |
| Combination units | | — | — | — | — | — | — |
| Power supply | | 3-phase, 380-415 V, 50 Hz | | | | | |
| Cooling capacity | Btu/h | 54,600 | 76,400 | 95,500 | 1,14,000 | 1,36,000 | 1,54,000 |
| | kW | 16.0 | 22.4 | 28.0 | 33.5 | 40.0 | 45.0 |
| Capacity control | % | 25-100 | 20-100 | 13-100 | 12-100 | 11-100 | 10-100 |
| Casing colour | | Ivory white (5Y7.5/1) | | | | | |
| Compressor | | Hermetically Sealed Scroll Type | | | | | |
| Type | | Hermetically Sealed Scroll Type | | | | | |
| No. of compressor | | 1 | 1 | 1 | 1 | 1 | 2 |
| Airflow rate | m ³ /min | 119 | 178 | 191 | 257 | | |
| Dimensions (HxWxD) | mm | 1,657X930X765 | | | | 1,657X1,240X765 | |
| Machine weight | kg | 165 | | 175 | | 220 | 260 |
| Sound level | dB(A) | 56 | 56 | 57 | 59 | 60 | 60 |
| Operation range | Cooling °CDB | 10 - 49 | | | | | |
| Refrigerant | Type | R410A | | | | | |
| Charge | kg | 5.9 | | 6.7 | 6.8 | 7.4 | 8.2 |
| Piping connections | Liquid | ø 9.5 | | | | ø 12.7 | |
| | Gas | ø 19.1 | | ø 22.2 | | ø 28.6 | |

Note: Specifications are based on the following conditions:



- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0
- Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m. During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS



Outdoor Units

VRV X (Cooling Only)

| | | |  | |  | | | |
|--------------------|--|---------------------|---|-----------|---|-----------|---------|--------|
| MODEL | | | RXQ18ARY1 | RXQ20ARY1 | RXQ22ARY1 | RXQ24ARY1 | | |
| Combination units | | | — | — | RXQ10ARY1 | RXQ12ARY1 | | |
| | | | — | — | RXQ12ARY1 | RXQ12ARY1 | | |
| | | | — | — | — | — | | |
| Power supply | | | 3-phase, 380-415 V, 50 Hz | | | | | |
| Cooling capacity | | Btu/h | 1,71,000 | 1,91,000 | 2,10,000 | 2,29,000 | | |
| | | kW | 50.0 | 56.0 | 61.5 | 67.0 | | |
| Capacity control | | % | 10-100 | 7-100 | 6-100 | | | |
| Casing colour | | | Ivory white (5Y7.5/1) | | | | | |
| Compressor | | | Hermetically Sealed Scroll Type | | | | | |
| | | Type | Hermetically Sealed Scroll Type | | | | | |
| | | No. of compressor | 2 | 2 | 1+1 | 1+1 | | |
| Airflow rate | | m ³ /min | 257 | 297 | 178+191 | 191+191 | | |
| Dimensions (HxWxD) | | mm | 1,657x1,240x765 | | (1,657x930x765)+(1,657x930x765) | | | |
| Machine weight | | kg | 260 | 285 | 175+175 | | | |
| Sound level | | dB(A) | 61 | 65 | 61 | 62 | | |
| Operation range | | Cooling °CDB | 10 ~ 49 | | | | | |
| Refrigerant | | | R410A | | | | | |
| | | Type | R410A | | | | | |
| | | Charge | kg | 8.4 | 11.8 | 6.7+6.8 | 6.8+6.8 | |
| Piping connections | | Liquid | mm | | | | ø 15.9 | |
| | | Gas | mm | | | | ø 28.6 | ø 34.9 |

Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Outdoor Units

VRV X (Cooling Only)

| | | |  | | |  | | | |
|--------------------|--|---------------------|---|-----------|-----------|---|-----------|-----------|---------|
| MODEL | | | RXQ26ARY1 | RXQ28ARY1 | RXQ30ARY1 | RXQ32ARY1 | RXQ34ARY1 | RXQ36ARY1 | |
| Combination units | | | RXQ12ARY1 | RXQ12ARY1 | RXQ12ARY1 | RXQ14ARY1 | RXQ16ARY1 | RXQ18ARY1 | |
| | | | RXQ14ARY1 | RXQ16ARY1 | RXQ18ARY1 | RXQ18ARY1 | RXQ18ARY1 | RXQ18ARY1 | |
| | | | — | — | — | — | — | — | |
| Power supply | | | 3-phase, 380-415 V, 50 Hz | | | | | | |
| Cooling capacity | | Btu/h | 2,47,000 | 2,68,000 | 2,85,000 | 3,05,000 | 3,24,000 | 3,41,000 | |
| | | kW | 73.5 | 78.5 | 83.5 | 90 | 95.0 | 100 | |
| Capacity control | | % | 6-100 | 5-100 | 5-100 | 5-100 | 4-100 | 5-100 | |
| Casing colour | | | Ivory white (5Y7.5/1) | | | | | | |
| Compressor | | | Hermetically Sealed Scroll Type | | | | | | |
| | | Type | Hermetically Sealed Scroll Type | | | | | | |
| | | No. of compressor | 1+1 | 1+2 | 1+2 | 1+2 | 2+2 | 2+2 | |
| Airflow rate | | m ³ /min | 191+257 | 191+257 | 191+257 | 257+257 | 257+257 | 257+257 | |
| Dimensions (HxWxD) | | mm | (1,657x930x765)+(1,657x1,240x765) | | | (1,657x1,240x765)+(1,657x1,240x765) | | | |
| Machine weight | | kg | 175+220 | 175+260 | | 220+260 | 260+260 | | |
| Sound level | | dB(A) | 63 | | | | 64 | | |
| Operation range | | Cooling °CDB | 10 ~ 49 | | | | | | |
| Refrigerant | | | R410A | | | | | | |
| | | Type | R410A | | | | | | |
| | | Charge | kg | 6.8+7.4 | 6.8+8.2 | 6.8+8.4 | 7.4+8.4 | 8.2+8.4 | 8.4+8.4 |
| Piping connections | | Liquid | mm | | ø 19.1 | ø 19.1 | ø 19.1 | ø 19.1 | ø 19.1 |
| | | Gas | mm | | ø 34.9 | ø 34.9 | ø 34.9 | ø 34.9 | ø 41.3 |

Note: Specifications are based on the following conditions:




- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS



Outdoor Units

VRV X (Cooling Only)


| | | | | | | |
|---|---|---|--------------|---|-------------|-------------|
|  |  |  | | | | |
| RXQ38ARY1 | RXQ40ARY1 | RXQ42ARY1 | RXQ44ARY1 | RXQ46ARY1 | RXQ48ARY1 | RXQ50ARY1 |
| RXQ18ARY1 | RXQ20ARY1 | RXQ12ARY1 | RXQ12ARY1 | RXQ14ARY1 | RXQ14ARY1 | RXQ14ARY1 |
| RXQ20ARY1 | RXQ20ARY1 | RXQ12ARY1 | RXQ12ARY1 | RXQ16ARY1 | RXQ16ARY1 | RXQ18ARY1 |
| — | — | RXQ18ARY1 | RXQ20ARY1 | RXQ18ARY1 | RXQ18ARY1 | RXQ18ARY1 |
| 3-phase, 380-415 V, 50 Hz | | | | | | |
| 3,62,000 | 3,82,000 | 3,99,000 | 4,20,000 | 4,40,000 | 4,57,000 | 4,78,000 |
| 106 | 112 | 117 | 123 | 129 | 134 | 140 |
| 4-100 | | 3-100 | | 4-100 | | 3-100 |
| Ivory white (5Y7.5/1) | | | | | | |
| Hermetically Sealed Scroll Type | | | | | | |
| 2+2 | | 1+1+2 | | | 1+2+2 | |
| 257+297 | 297+297 | 191+191+257 | 191+191+297 | 257+257+257 | | |
| (1,657X1,240X765)+ (1,657X1,240X765) | | (1,657X930X765)+ (1,657X930X765)+ (1,657X1,240X765) | | (1,657X1,240X765)+ (1,657X1,240X765)+ (1,657X1,240X765) | | |
| 260+285 | 285+285 | 175+175+260 | 175+175+285 | 220+220+260 | 220+260+260 | 220+260+260 |
| 66 | 68 | 65 | 67 | 65 | | |
| 10 ~ 49 | | | | | | |
| R410A | | | | | | |
| 8.4+11.8 | 11.8+11.8 | 6.8+6.8+8.4 | 6.8+6.8+11.8 | 7.4+7.4+11.8 | 7.4+8.2+8.4 | 7.4+8.4+8.4 |
| ø 19.1 | | | | | | |
| ø 41.3 | | | | | | |

Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Outdoor Units

VRV X (Cooling Only)

| | | | | | | |
|---|---------------------------|---|-------------|-------------|--------------|--------------------------------|
|  | | | | | | |
| MODEL | RXQ52ARY1 | RXQ54ARY1 | RXQ56ARY1 | RXQ58ARY1 | RXQ60ARY1 | |
| Combination units | RXQ16ARY1 | RXQ18ARY1 | RXQ18ARY1 | RXQ18ARY1 | RXQ20ARY1 | |
| | RXQ18ARY1 | RXQ18ARY1 | RXQ18ARY1 | RXQ20ARY1 | RXQ20ARY1 | |
| | RXQ18ARY1 | RXQ18ARY1 | RXQ20ARY1 | RXQ20ARY1 | RXQ20ARY1 | |
| Power supply | 3-phase, 380-415 V, 50 Hz | | | | | |
| Cooling capacity | Btu/h | 4,95,000 | 5,12,000 | 5,32,000 | 5,53,000 | 5,73,000 |
| | kW | 145 | 150 | 156 | 162 | 168 |
| Capacity control | % | 3-100 | | | 2-100 | |
| Casing colour | Ivory white (5Y7.5/1) | | | | | |
| Compressor | Type | Hermetically Sealed Scroll Type | | | | |
| | No. of compressor | 2+2+2 | | | | |
| Airflow rate | m ³ /min | 257+257+257 | | 257+297+297 | | |
| Dimensions (HxWxD) | mm | (1,657x1,240x765 + 1,657x1,240x765 + 1,657x1,240x765) | | | | |
| Machine weight | kg | 260+260+260 | 260+260+285 | 260+285+285 | 285+285+285 | |
| Sound level | dB(A) | 65 | 66 | 68 | 69 | 70 |
| Operation range | Cooling | °CDB | | | | 10 ~ 49 |
| | Refrigerant | R410A | | | | |
| Piping connections | Type | R410A | | | | |
| | Charge | kg | 8.2+8.4+8.4 | 8.4+8.4+8.4 | 8.4+8.4+11.8 | 8.4+11.8+11.8 11.8+11.8+11.8 |
| Liquid | mm | ø 19.1 | | | | |
| | Gas | mm | ø 41.3 | | | |

Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0 m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS



Outdoor Units

VRV X (Heat Pump)

| MODEL | | RXYQ6ARY6 | RXYQ8ARY6 | RXYQ10ARY6 | RXYQ12ARY6 | RXYQ14ARY6 | RXYQ16ARY6 |
|--------------------|---------------------|---------------------------------|-----------|------------|------------|-----------------|------------|
| Combination units | | — | — | — | — | — | — |
| Power supply | | 3-phase, 380-415 V, 50 Hz | | | | | |
| Cooling capacity | Btu/h | 54,600 | 76,400 | 95,500 | 1,14,000 | 1,36,000 | 1,54,000 |
| | kW | 16.0 | 22.4 | 28.0 | 33.5 | 40.0 | 45.0 |
| Heating capacity | Btu/h | 61,400 | 85,300 | 1,07,000 | 1,28,000 | 1,54,000 | 1,71,000 |
| | kW | 18.0 | 25.0 | 31.5 | 37.5 | 45.0 | 50.0 |
| Capacity control | % | 25-100 | 20-100 | 13-100 | 12-100 | 11-100 | 10-100 |
| Casing colour | | Ivory white (5Y7.5/1) | | | | | |
| Compressor | Type | Hermetically Sealed Scroll Type | | | | | |
| | No. of compressor | 1 | | | 2 | | |
| Airflow rate | m ³ /min | 119 | 178 | 191 | 257 | | |
| Dimensions (HxWxD) | mm | 1,657X930X765 | | | | 1,657X1,240X765 | |
| Machine weight | kg | 180 | 195 | | 265 | | |
| Sound level | dB(A) | 56 | 57 | | 60 | | |
| Operation range | Cooling | °CDB | | -5 ~ 49 | | | |
| | Heating | °CDB | | -20 ~ 15.5 | | | |
| Refrigerant | Type | R410A | | | | | |
| | Charge | kg | 6.9 | 7.0 | 7.4 | 7.6 | 9.1 |
| Piping connections | Liquid | mm | ø 9.5 | | | ø 12.7 | |
| | Gas | mm | ø 19.1 | | ø 22.2 | | ø 28.6 |

Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0.
 - Heating: Indoor temp.: 20°CDB, Outdoor temp.: 7°CDB, 6°WB, Equivalent piping length: 7.5m, Level difference: 0m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Outdoor Units

VRV X (Heat Pump)

| MODEL | | RXYQ18ARY6 | RXYQ20ARY6 | RXYQ22ARY6 | RXYQ24ARY6 |
|--------------------|---------------------|---------------------------------|------------|---------------------------------|------------|
| Combination units | | — | — | RXYQ10ARY6 | RXYQ12ARY6 |
| | | — | — | RXYQ12ARY6 | RXYQ12ARY6 |
| | | — | — | — | — |
| Power supply | | 3-phase, 380-415 V, 50 Hz | | | |
| Cooling capacity | Btu/h | 1,71,000 | 1,91,000 | 2,10,000 | 2,29,000 |
| | kW | 50.0 | 56.0 | 61.5 | 67.0 |
| Heating capacity | Btu/h | 1,91,000 | 2,15,000 | 2,35,000 | 2,56,000 |
| | kW | 56.0 | 63.0 | 69.0 | 75.0 |
| Capacity control | % | 10-100 | 7-100 | 6-100 | |
| Casing colour | | Ivory white (5Y7.5/1) | | | |
| Compressor | Type | Hermetically Sealed Scroll Type | | | |
| | No. of compressor | 2 | | 1+1 | |
| Airflow rate | m ³ /min | 257 | 297 | 178+191 | 191+191 |
| Dimensions (HxWxD) | mm | 1,657X1,240X765 | | (1,657X930X765)+(1,657X930X765) | |
| Machine weight | kg | 285 | 305 | 195+195 | |
| Sound level | dB(A) | 61 | 65 | 61 | 62 |
| Operation range | Cooling | °CDB | | -5 ~ 49 | |
| | Heating | °CDB | | -20 ~ 15.5 | |
| Refrigerant | Type | R410A | | | |
| | Charge | kg | 11.8 | 7.4+7.6 | 7.6+7.6 |
| Piping connections | Liquid | mm | ø 15.9 | | |
| | Gas | mm | ø 28.6 | | ø 34.9 |

Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0.
 - Heating: Indoor temp.: 20°CDB, Outdoor temp.: 7°CDB, 6°WB, Equivalent piping length: 7.5m, Level difference: 0m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS



Outdoor Units

VRV X (Heat Pump)

| MODEL | | RXYQ26ARY6 | RXYQ28ARY6 | RXYQ30ARY6 | RXYQ32ARY6 | RXYQ34ARY6 | RXYQ36ARY6 |
|--------------------|---------------------|-----------------------------------|------------|------------|-------------------------------------|------------|--------------------|
| Combination units | RXYQ12ARY6 | RXYQ12ARY6 | RXYQ12ARY6 | RXYQ16ARY6 | RXYQ16ARY6 | RXYQ16ARY6 | RXYQ16ARY6 |
| | RXYQ14ARY6 | RXYQ16ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ20ARY6 | RXYQ20ARY6 |
| Power supply | | 3-phase, 380-415 V, 50 Hz | | | | | |
| Cooling capacity | Btu/h | 2,47,000 | 2,68,000 | 2,85,000 | 3,05,000 | 3,24,000 | 3,45,000 |
| | kW | 73.5 | 78.5 | 83.5 | 90.0 | 95.0 | 101.0 |
| Heating capacity | Btu/h | — | 2,99,000 | 3,19,000 | 3,41,000 | 3,62,000 | 3,86,000 |
| | kW | 82.5 | 87.5 | 93.5 | 100.0 | 106.0 | 113.0 |
| Capacity control | % | 5-100 | | | | | 4-100 |
| Casing colour | | Ivory white (5Y7.5/1) | | | | | |
| Compressor | Type | Hermetically Sealed Scroll Type | | | | | |
| | No. of compressor | 1+2 | | | 2+2 | | |
| Airflow rate | m ³ /min | 191+257 | | | 257+257 | | 257+297 |
| Dimensions (HxWxD) | mm | (1,657X930X765)+(1,657X1,240X765) | | | (1,657X1,240X765)+(1,657X1,240X765) | | |
| Machine weight | kg | 195+265 | 195+285 | 265+265 | 265+285 | 265+305 | |
| Sound level | dB(A) | 63 | | | 64 | | 66 |
| Operation range | Cooling | °CDB -5 ~ 49 | | | | | |
| | Heating | °CDB -20 ~ 15.5 | | | | | |
| Refrigerant | Type | R410A | | | | | |
| | Charge | kg | 7.6+9.1 | 7.6+9.3 | 7.6+11.8 | 9.3+9.3 | 9.3+11.8 |
| Piping connections | Liquid | mm \varnothing 19.1 | | | | | |
| | Gas | mm \varnothing 34.9 | | | | | \varnothing 41.3 |

Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0.
 - Heating: Indoor temp.: 20°CDB, Outdoor temp.: 7°CDB, 6°WB, Equivalent piping length: 7.5m, Level difference: 0m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

Outdoor Units

VRV X (Heat Pump)

| MODEL | | RXYQ38ARY6 | RXYQ40ARY6 | RXYQ42ARY6 | RXYQ44ARY6 |
|--------------------|---------------------|-------------------------------------|------------|---|-------------|
| Combination units | RXYQ18ARY6 | RXYQ20ARY6 | RXYQ12ARY6 | RXYQ12ARY6 | |
| | RXYQ20ARY6 | RXYQ20ARY6 | RXYQ12ARY6 | RXYQ12ARY6 | |
| Power supply | | 3-phase, 380-415 V, 50 Hz | | | |
| Cooling capacity | Btu/h | 3,62,000 | 3,82,000 | 3,99,000 | 4,20,000 |
| | kW | 106.0 | 112.0 | 117.0 | 123.0 |
| Heating capacity | Btu/h | 4,06,000 | 4,30,000 | 4,47,000 | 4,71,000 |
| | kW | 119.0 | 126.0 | 131.0 | 138.0 |
| Capacity control | % | 4 - 100 | 3 - 100 | 4 - 100 | 3 - 100 |
| Casing colour | | Ivory white (5Y7.5/1) | | | |
| Compressor | Type | Hermetically Sealed Scroll Type | | | |
| | No. of compressor | 2+2 | | 1+1+2 | |
| Airflow rate | m ³ /min | 257+297 | 297+297 | 191+191+257 | 191+191+297 |
| Dimensions (HxWxD) | mm | (1,657X1,240X765)+(1,657X1,240X765) | | (1,657X930X765)+(1,657X930X765)+(1,657X1,240X765) | |
| Machine weight | kg | 285+305 | 305+305 | 195+195+285 | 200+200+325 |
| Sound level | dB(A) | 66 | 68 | 65 | 67 |
| Operation range | Cooling | °CDB -5 ~ 49 | | | |
| | Heating | °CDB -20 ~ 15.5 | | | |
| Refrigerant | Type | R410A | | | |
| | Charge | kg | 11.8+11.8 | 7.6+7.6+11.8 | |
| Piping connections | Liquid | mm \varnothing 19.1 | | | |
| | Gas | mm \varnothing 41.3 | | | |



Note: Specifications are based on the following conditions:

- Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0.
 - Heating: Indoor temp.: 20°CDB, Outdoor temp.: 7°CDB, 6°WB, Equivalent piping length: 7.5m, Level difference: 0m.
 - Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
- During actual operation, these values are normally somewhat higher as a result of ambient conditions.

SPECIFICATIONS

Outdoor Units

VRV X (Heat Pump)

| | | | | | | | |
|---|-------------|--------------|---|--|-------------|-------------|-------------|
|  | | | |  | | | |
| RXYQ46ARY6 | RXYQ48ARY6 | RXYQ50ARY6 | RXYQ52ARY6 | RXYQ54ARY6 | RXYQ56ARY6 | RXYQ58ARY6 | RXYQ60ARY6 |
| RXYQ14ARY6 | RXYQ16ARY6 | RXYQ16ARY6 | RXYQ16ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ20ARY6 |
| RXYQ16ARY6 | RXYQ16ARY6 | RXYQ16ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ20ARY6 | RXYQ20ARY6 |
| RXYQ16ARY6 | RXYQ16ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ18ARY6 | RXYQ20ARY6 | RXYQ20ARY6 | RXYQ20ARY6 |
| 3-phase, 380-415 V, 50 Hz | | | | | | | |
| 4,44,000 | 4,61,000 | 4,78,000 | 4,95,000 | 5,12,000 | 5,32,000 | 5,53,000 | 5,73,000 |
| 130.0 | 135.0 | 140.0 | 145.0 | 150.0 | 156.0 | 162.0 | 168.0 |
| 4,95,000 | 5,12,000 | 5,32,000 | 5,53,000 | 5,73,000 | 5,97,000 | 6,21,000 | 6,45,000 |
| 145.0 | 150.0 | 156.0 | 162.0 | 168.0 | 175.0 | 182.0 | 189.0 |
| 3 - 100 | | | | 2 - 100 | | | |
| Ivory white (5Y7.5/1) | | | | | | | |
| Hermetically Sealed Scroll Type | | | | | | | |
| 2+2+2 | | | | | | | |
| 257+257+257 | | 257+257+297 | | 257+257+257 | | 257+257+297 | 257+297+297 |
| (1,657X1,240X765)+ (1,657X1,240X765)+ (1,657X1,240X765) | | | (1,657X1,240X765 + 1,657X1,240X765 + 1,657X1,240X765) | | | | |
| 195+195+305 | 265+265+265 | 265+265+285 | 265+285+285 | 285+285+285 | 285+285+305 | 285+305+305 | 305+305+305 |
| 65 | | | 66 | | 68 | 69 | 70 |
| -5 ~ 49 | | | | | | | |
| -20 ~ 15.5 | | | | | | | |
| R410A | | | | | | | |
| 9.1+9.3+9.3 | 9.3+9.3+9.3 | 9.3+9.3+11.8 | 9.3+11.8+11.8 | 11.8+11.8+11.8 | | | |
| ø 19.1 | | | | | | | |
| ø 41.3 | | | | | | | |

Note: Specifications are based on the following conditions:
 • Cooling: Indoor temp.: 27°CDB, 19°CWB, Outdoor temp.: 35°CDB, Equivalent piping length: 7.5 m, Level difference: 0.
 • Heating: Indoor temp.: 20°CDB, Outdoor temp.: 7°CDB, 6°WB, Equivalent piping length: 7.5m, Level difference: 0m.
 • Sound level: Anechoic chamber conversion value, measured at a point 1 m in front of the unit at a height of 1.5 m.
 During actual operation, these values are normally somewhat higher as a result of ambient conditions.